

THOMSON  DELPHION		RESEARCH My Account Products	PRODUCTS Search: Quick/Number Boolean Advanced Derwent	INSIDE DELPHION
--	--	--	--	------------------------

The Delphion Integrated View

 Get Now: ☒ PDF | [More choices...](#)

 Tools: Add to Work File: [Create new Work File](#)

 View: [INPADOC](#) | Jump to: [Top](#) Go to: [Derwent](#)
[Email this to a](#)
Title: JP9237616A2: MANGANESE DRY BATTERY
Derwent Title: Manganese dry battery for portable electric appliances - has cyclic packing containing paper with predefined density as base material that is impregnated with water repellent matter [\[Derwent Record\]](#)
Country: JP Japan

Kind: A

Inventor: TAKAHASHI HIROYUKI;
SUZUKI HIROKO;

Assignee: TOSHIBA BATTERY CO LTD
[News, Profiles, Stocks and More about this company](#)
Published / Filed: 1997-09-09 / 1996-02-27

Application Number: JP1996000040155

IPC Code: H01M 2/08; H01M 6/08;

Priority Number: 1996-02-27 JP1996000040155

Abstract: PROBLEM TO BE SOLVED: To provide a dry battery with a good yield further with high reliability by attaining improvement of a liquid leak resistance characteristic of a packing seal part.


 SOLUTION: This dry battery is constituted by providing a sheathing can 11 and a negative electrode terminal plate 8 mounting liquid-tightly a peripheral edge part in a lower part flexed end internal wall surface of the sheathing can 11 through a heat shrinkage resin layer 10 and an annular packing 9. Here, the annular packing 9 is formed so as to be impregnated with at least 35wt.% a water repellent substance with a paper material of 0.4 to 0.6g/cm³ density serving as the base material further with the substance comprising a mixture of 1 to 3wt.% polyvinyl alcohol, 9 to 27wt.% polybutene and 70 to 90wt.% paraffin wax.


COPYRIGHT: (C)1997,JPO

Family: None

Best Available Copy

Forward References: Go to Result Set: [Forward references \(1\)](#)

PDF	Patent	Pub.Date	Inventor	Assignee	Title
	US6586912	2003-07-01	Tsukamoto; Hisashi	Quallion LLC	Method and apparatus for amplitude limiting battery temperature spikes

Other Abstract Info: CHEMABS 127(18)250659V CAN127(18)250659V DERABS C97-500347 DERC97-500347




[Nominate this for the Gallery...](#)



© 1997-2004 Thomson

[Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)



(19)

(11) Publication number:

092376

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **08040155**(51) Intl. Cl.: **H01M 2/08 H01M 6/08**(22) Application date: **27.02.96**

(30) Priority:

(43) Date of application
publication: **09.09.97**(84) Designated contracting
states:(71) Applicant: **TOSHIBA BATTERY CO LTD**(72) Inventor: **TAKAHASHI HIROYUKI**
SUZUKI HIROKO

(74) Representative:

**(54) MANGANESE DRY
BATTERY**


(57) Abstract:

PROBLEM TO BE SOLVED: To provide a dry battery with a good yield further with high reliability by attaining improvement of a liquid leak resistance characteristic of a packing seal part.

SOLUTION: This dry battery is constituted by providing a sheathing can 11 and a negative electrode terminal plate 8 mounting liquid-tightly a peripheral edge part in a lower part flexed end internal wall surface of the sheathing can 11 through a heat shrinkage resin layer 10 and an annular packing 9. Here, the annular packing 9 is formed so as to be impregnated with at least 35wt.% a water repellent substance with a paper material of 0.4 to 0.6g/cm³ density serving as the base material further with the substance comprising a mixture of 1 to 3wt.% polyvinyl alcohol, 9 to 27wt.% polybutene and 70 to 90wt.% paraffin

wax.

COPYRIGHT: (C)1997,JPO



Best Available Copy